

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification 6 : G11B 5/31, 5/187, 5/255</p>	<p>A1</p>	<p>(11) International Publication Number: WO 98/00840 (43) International Publication Date: 8 January 1998 (08.01.98)</p>
<p>(21) International Application Number: PCT/KR97/00113 (22) International Filing Date: 13 June 1997 (13.06.97) (30) Priority Data: 1996/25198 28 June 1996 (28.06.96) KR 1996/25200 28 June 1996 (28.06.96) KR 1996/30874 27 July 1996 (27.07.96) KR (71) Applicant (for all designated States except US): SAMSUNG ELECTRONICS CO., LTD. [KR/KR]; 416, Maetan-dong, Paldal-gu, Suwon-city, Kyungki-do 442-373 (KR). (72) Inventors; and (73) Inventors/Applicants (for US only): LEE, Jae, Soo [KR/KR]; 103-1704, Chunggu Apartment, Kwangjang-dong, Kwangjin-gu, Seoul 143-210 (KR). KIM, Sang, Joon [KR/KR]; 416, Maetan 3-dong, Paldal-gu, Suwon-city, Kyungki-do 442-373 (KR). CHUNG, Byung, Soo [KR/KR]; 2-705, Youngkwang Apartment, 220-4, Hwaseo 1-dong, Jangan-gu, Suwon-city, Kyungki-do 440-151 (KR). (74) Agent: LEE, Young, Pil; The Cheonghwa Building, 1571-18, Seocho-dong, Seocho-gu, Seoul 137-073 (KR).</p>		<p>(81) Designated States: CN, DE, JP, SG, US.  Published With international search report.</p>
<p>(54) Title: THIN FILM MAGNETIC HEAD TIP AND MANUFACTURING METHOD THEREFOR (57) Abstract A thin film magnetic head tip, and a method for manufacturing the thin film magnetic head tip by a wafer process, are provided. A base (120) material is stacked on a wafer (100) and a core (110) is stacked partially within the base material to form an azimuth groove (140). Conductive points (210) are within a plurality of holes passed through the wafer (100). A coil (130) is stacked being connected to the conductive points (210), and the surface of the core (110) with the azimuth angle and the base (120) are rounded.</p> <div data-bbox="941 1050 1429 1764"> </div>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## THIN FILM MAGNETIC HEAD TIP AND MANUFACTURING METHOD THEREFOR

### 5 Technical Field

The present invention relates to a thin film magnetic head tip of a videocassette recorder (VCR), used for recording/reproducing information onto/from a tape and a manufacturing method therefor.

### 10 Background Art

Generally, a VCR includes a head drum 2 as shown in FIG. 1 for diagonally scanning a magnetic tape 1 with respect to the traveling direction thereof in order to read information recorded on the traveling magnetic tape 1 or record new information onto the magnetic tape 1.

15 The head drum 2 includes a fixed drum 3 for guiding the magnetic tape 1, a rotary drum 4 rotatably installed on a shaft of the fixed drum 3 and a magnetic head 5 installed in the rotary drum 4. Also, as shown in FIG. 1, the magnetic head 5 includes a head base 6 and a magnetic head tip 7.

Referring to FIG. 2, the magnetic head tip 7 is manufactured by various  
20 processes. That is, cores 9 and 9' are manufactured separately and the spacing between the cores 9 and 9' is determined after lapping, bonding and assembly processes.

However, the above magnetic head tip 7 and the manufacturing method therefor are not desirable due to various errors and deviations caused during the  
25 various processes. Also, since the cores 9 and 9' should be formed of ferrite, it is difficult to minimize the size of the core 9 and 9'.

To solve this problem, in Korean Patent Application No. 95-2081, filed Feb. 6, 1995, entitled "magnetic head and manufacturing method therefor", there is described a magnetic layer which is selectively formed, so that a magnetic path  
30 is shortened, reducing inductance. Also, a separate manufacturing process for two cores is not required, improving yield.

However, the method for manufacturing the magnetic head includes various

processing steps as before: the step of attaching a substrate member processed to have a predetermined azimuth angle to the uppermost layer of a stacked structure, the step of forming a window for winding, the step of machining one side of the magnetic head in a predetermined curvature in order to improve the contact to a tape, and the step of performing the winding.

#### Disclosure of the Invention

It is an object of the present invention to provide a thin film magnetic head tip and a manufacturing method therefor, which reduces the manufacturing steps of a magnetic head and makes possible the mass production of the magnetic head.

According to an aspect of the present invention, there is provided a thin film magnetic head tip comprising: a wafer being a non-magnetic insulator; a conductive contact point within a plurality of holes formed through the wafer; a base being a non-magnetic insulator, stacked on the wafer; a magnetic core being partially within the base, having an azimuth groove; and a coil within the base wound around the core, having two ends each connected to the conductive contact points.

According to another aspect of the present invention, there is provided a method for manufacturing a thin film magnetic head tip comprising the steps of: (a) forming a plurality of holes passing through a wafer; (b) filling the holes with a conductive material; (c) stacking a base being a non-magnetic insulator, a magnetic core having an azimuth groove, and a coil within the base around the magnetic core on the wafer in a predetermined shape by a wafer process; and (d) cutting the stacked wafer into thin film magnetic head tips.

In the thin film magnetic head tip and the manufacturing method therefor according to the present invention, the manual manufacturing steps for the magnetic head are reduced and the mass production of the magnetic head is achieved effectively.

#### Brief Description of the Drawings

FIG. 1 is a perspective view of a head drum for a videocassette recorder (VCR);

FIG. 2 is a perspective view of the magnetic head tip of FIG. 1;

FIG. 3 is a partially cutaway perspective view of a wafer used for a thin film magnetic head tip according to the present invention;

FIG. 4 is a sectional view illustrating the step of stacking to form a thin film magnetic head tip of the present invention by a wafer process;

5        FIG. 5 is a perspective view of a wafer plate in which the thin film magnetic head tip of the present invention is formed by stacking;

FIG. 6 is a perspective view of the thin film magnetic head tip obtained by cutting the wafer plate of FIG. 5; and

10       FIG. 7 is a perspective view showing a step in which the thin film magnetic head tip of the present invention is attached to a head base.

#### Best mode for carrying out the Invention

A thin film magnetic head tip according to the present invention is manufactured by a well-known wafer process. As shown in FIG. 4, the wafer process is for sequentially stacking predetermined material onto a wafer 100 of  
15       FIG. 3 using sputtering, deposition and photolithography processes.

As shown in FIGS. 3 and 7, holes formed through the wafer 100 used for the wafer process are filled with metal such as copper (Cu). One side of the metal is used as a contact point 210 when connecting a thin film magnetic head tip 200  
20       to a head base 300. The other side of the metal is connected to a conductive coil 130 (see FIG. 4) which will be described later.

Referring to FIG. 4, a magnetic core 110, a base 120 being a non-magnetic insulator and a conductive coil 130 are stacked on the wafer 100 in a predetermined shape by deposition and photolithography methods.

25       The conductive coil 130 is formed within the base 120 around the magnetic core 110, and two ends of the conductive coil 130 are connected to two of the contact points 210 formed on the wafer 100, respectively. That is, the conductive coil 130 is stacked together with the base 120 and the magnetic core 110 while winding the magnetic core 110.

30       The magnetic core 110 is formed of iron (Fe) compounds or amorphous alloy containing cobalt (Co) having high magnetic permeability, high saturation magnetic flux density and less coercive force, and the base 120 being the non-

magnetic insulator is a material having a thermal expansion coefficient which is similar to that of the material used for the magnetic core 110, and a strong antiabrasion property. Also, the conductive coil 130 is formed of metal such as Cu having high conductivity.

5 Referring to FIG. 4, in the final step, an azimuth groove 140 and a curved surface 150 are formed atop the magnetic core 110. The azimuth groove 140 and the curved surface 150 are intentionally formed by deposition and photolithography processes. The magnetic cores 110 are separated from each other by the azimuth groove 140, and the curved surface 150 contacts the magnetic tape 1 of FIG. 1.

10 When the curved surface 150 is formed by the deposition and photolithography methods, a staircase texture 151 is formed on the curved surface 150 as shown in the enlarged view of FIG. 4. However, since the height of a staircase texture 151 is below several micrometers, the curved surface 150 is capable of smoothly contacting the magnetic tape 1 of FIG. 1.

15 As described above, a wafer plate 400 of FIG. 5, manufactured by the wafer process, is cut into a plurality of thin film magnetic head tips 200 of FIG. 6 of a proper size by a cutter (not shown). The azimuth groove 140 is formed in the curved surface 150 formed on the thin film magnetic head tip 200. Even though the number of thin film magnetic head tips obtained from one wafer plate is dependent on the size of the wafer plate, several hundreds of thin film magnetic head tips 200 are obtained from one wafer plate in general.

20 As described above, the thin film magnetic head tip 200 obtained by cutting the wafer plate manufactured by the wafer process is attached to the head base 300 as shown in FIG. 7.

25

#### Industrial Applicability

According to the thin film magnetic head tip and the manufacturing method therefor, the number of manual processes for manufacturing the magnetic head is reduced and the magnetic head can be effectively produced by mass production.

30 In particular, the manufacturing process is simplified since additional processes for forming the curved surface contacting the magnetic tape are not required.

CLAIMS:

1. A thin film magnetic head tip comprising:  
a wafer (100) being a non-magnetic insulator;  
a conductive contact point (210) within a plurality of holes formed through  
5 the wafer (100);  
a base (120) being a non-magnetic insulator, stacked on the wafer;  
a magnetic core (110) being partially within the base (120), having an  
azimuth groove (140); and  
a coil (130) within the base (120) wound around the core, having two ends  
10 each connected to the conductive contact points (210).
2. A thin film magnetic head tip as claimed in claim 1, comprising a  
curved surface (150) formed being curved together with the surface of the magnetic  
core (110) with the azimuth groove (140) and the base (120).
3. A thin film magnetic head tip as claimed in claim 1 or 2, wherein the  
15 conductive contact point (120) is formed of metal.
4. A method for manufacturing a thin film magnetic head tip comprising  
the steps of:  
(a) forming a plurality of holes passing through a wafer (100);  
(b) filling the holes with a conductive material;  
20 (c) stacking a base (120) being a non-magnetic insulator, a magnetic core  
(110) having an azimuth groove (140), and a coil (130) within the base (120)  
around the magnetic core (110) on the wafer (100) in a predetermined shape by a  
wafer process; and  
(d) cutting the stacked wafer into thin film magnetic head tips.
- 25 5. A method for manufacturing a thin film magnetic head tip as claimed in  
claim 4, wherein the magnetic core (110) and the base (120) are stacked in a  
staircase shape to form a curved surface (150) curved together with the surface of  
the magnetic core (110) with the azimuth groove (140) and the base (120) during  
the step (c).
- 30 6. A method for manufacturing a thin film magnetic head tip as claimed in  
claim 4 or 5, wherein in the step (c), a predetermined material is sequentially  
deposited on the wafer (100) in a predetermined shape by deposition and



photolithography methods.

FIG. 1




FIG. 2




FIG. 3





FIG. 4



4 / 5

FIG. 5






FIG. 6



5 / 5

FIG. 7



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR 97/00113

## A. CLASSIFICATION OF SUBJECT MATTER

IPC<sup>6</sup>: G 11 B 5/31, 5/187, 5/255

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC<sup>6</sup>: G 11 B 5/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPIL

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 583 921 A1 (IBM) 23 February 1994 (23.02.94), abstract; fig.3-5; column 8, line 1 - column 11, line 3.	1-6
A	EP 0 515 786 A1 (READ-RITE CORP.) 02 December 1992 (02.12.92), abstract; fig.1-5; column 3, line 18 - column 4, line 13.	1-6
A	EP 0 407 244 A1 (THOMSON-CSF) 09 January 1991 (09.01.91), abstract; fig.1-15. -----	1-6

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

18 September 1997 (18.09.97)

Date of mailing of the international search report

02 October 1997 (02.10.97)

Name and mailing address of the ISA/AT

AUSTRIAN PATENT OFFICE

Kohlmarkt 8-10

A-1014 Vienna

Facsimile No. 1/53424/535

Authorized officer

Berger

Telephone No. 1/53424/453

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.

PCT/KR 97/00113

Im Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
EP A1 583921	23-02-94	JF A2 6168414 US A 5648696 US A 5655286	14-06-94 23-01-96 12-08-97
EP A1 515786	02-12-92	DE C0 69220289 DE T2 69220289 EP B1 515786 JF A2 5132112 US A 5670747	17-07-97 25-09-97 11-06-97 18-06-97 17-08-98
EP A1 407244	09-01-91	DE C0 69012005 DE T2 69012005 EP B1 407244 JF A1 5549526 JF B1 5549526 JF A2 5116508 US A 5667230	06-10-94 06-10-95 01-08-94 11-01-91 20-09-91 17-05-91 26-11-91